



United States
513.731.1110

France
+33(0) 3.29.37.88.22

Japan
81.3.3344.3010

China
86.21.6064.9669

BiLUBE® 8109

Technical Specifications

Bismuth	19.7 - 20.3%
Nonvolatiles @ 105°C	85% min
Color (Gardner)	10 max.
Specific Gravity @ 25°C	1.15 - 1.21
Viscosity (Brookfield) @25°C	100 Pse

Product Number

1379L

Description:

Liquid ranging in color from pale yellow to light brown with a fatty acid musty odor.

Application:

Lubricant

Packaging:

500 lb - 55 gallon steel closed head drum

Chemical Formula:

Manufactured under ISO 9001 registered quality management systems.

Description

Bismuth carboxylates are readily soluble in hydrocarbon solvents, including many lubricant base oils (e.g. Group II/III, PAO). Bismuth carboxylates are also effective extreme-pressure (EP) lubricant additives in greases and oils, providing improved lubricity and anti-wear benefits in moving metal parts (e.g. pistons, gears). It has been shown that bismuth carboxylates, especially bismuth neodecanoate (Bi NDA) and bismuth 2-ethylhexanoate (Bi Oct) have excellent synergistic EP properties when combined with a variety of sulfur-based additives. For example, Bi NDA (5 wt%) and polysulfide-based active sulfur (1 wt%) give excellent 4-Ball Weld Load results while also providing modest anti-wear activity when used in a Group II base oil system. Please see our peer-reviewed article for more details: Bismuth Sulfide (Bi2S3) as the Active Species in Extreme Pressure Lubricants Containing Bismuth Carboxylates and Sulfur Compounds. R. T. Hart, A. A. Kerr, N. A. Eckert. Trib. Trans. 2010, 53 (1), 22 – 28.

4900 Beech Street, Norwood OH 45212 • P:513-731-1110 • www.shepchem.com

The management system governing the manufacture of this product is ISO 9001:2015 and RCMS®:2013 certified.