

**United States** 513.731.1110

**France** +33(0) 3.29.37.88.22

**Japan** 81.3.3344.3010

**China** 86.21.6064.9669

# **Copper Iodide, Technical Grade**

# **Technical Specifications**

Copper 32.6% min.

Iron 200 ppm max.

Sulfate 1000 ppm max.

Moisture @ 105°C 1.0 % max.

Ammonium

Hydroxide Insolubles 1000 ppm max.

#### **Product Number**

1232

#### **Description:**

powder ranging in color from white to brownish-yellow or tan. Soluble in ammonia and potassium iodide solutions; insoluble in water

#### **Application:**

**Specialty Polymers** 

# Packaging:

100lb - 26 gallon fiber drum

### **Chemical Formula:**

Manufactured under ISO 9001 registered quality management systems.

## **Description**

As the marketplace drives demand for new applications, Shepherd Chemical continuously develops new polymer additives to provide for changes in industry requirements. Technical Grade Copper lodide is used as a catalyst, and nylon heat stabilizer. Common applications include: electroplating, dyes, heat stabilizers and catalysts.

4900 Beech Street, Norwood OH 45212 • P:513-731-1110 • www.shepchem.com

The management system governing the manufacture of this product is ISO 9001:2015 and RCMS®:2013 certified.